

Prime Fixed Generator 20

20 (kVA) 50HZ 1500RPM



SPECIFICATIONS

ALTERNATOR

Frequency	50 Hz
Output Rating	20 kVA
Voltage	50Hz:100/200 or 110/220V
Rotating Speed	1500 rpm
Power Factor	1
No. of Phase	Single Phase 3 Wire
Rating	Continuous
Excitation	Brushless, (with A.V.R.)
No. Poles	4

ENGINE

Make & Model	Kubota V2203-KB
Type	Inlined, Swirl Chambered
No. of Cylinders-Bore X Stroke	4 - 87 x 92.4 mm
Piston Displacement	2.197L
Rated Output	25/1500 PS/rpm
Battery	80D26R x 1
Fuel	Diesel
Fuel Capacity	62L
Fuel Consumption	3.9 L/H

UNIT

Dimensions (L/W/H)	1540 x 650 x 900
Dry Weight	591kg

GENERAL

The DCA series generators are complete, stand alone generating sets. All models consist of an alternator which is directly coupled to a diesel engine. The alternator and engine are set on a common skid base. Special Vibration isolators are used to minimize vibrations during operation. The generator and electrical components are fully enclosed in a solid steel, weatherproof canopy. Noise suppression is achieved by using highly effective sound insulation materials.

50HZ/60HZ OPERATION

The DCA series can be operated at either 50Hz or 60Hz by simply adjusting the engine speed using the throttle control knob on the control panel.

AUTO FUEL AIR EXTRACTOR

Air trapped in the fuel system can be troublesome. However, with the DCA series, fuel air extraction is Automatically performed by simply operating the starter switch, without the need for tools or devices. There is no soiling of the machines interior or the operators hands and the outflow of fuel to the machines exterior is prevented. The machine will start after the engine is turned over a few times.

EXTREMELY QUIET OPERATION

In urban areas and at the worksite, there is an ever increasing demand for reduced noise. The DCA series generators are extremely quiet when operating at full load.

CLEAN ENGINES

The engines used in these generators meet all Californian Atmospheric Pollution standards, which is one of the worlds most stringent antipollution standards. This is achieved by using a PCV purge control valve system. Therefore, these engines do not discharge blow-by gas to the outside, which keeps the interior of the machine cleaner and the exhaust emissions are minimized