



Prime Fixed Generator 40

37 (kVA) 50HZ 1500RPM



SPECIFICATIONS

ALTERNATOR

Frequency	Hz 50
Output Rating	
Continuous	37kVA
Standby	38.9kVA
NO.of Phases	Three-Phases. 4Wire
Rated Voltage	V Line to line 50Hz: 190-215(220) or 380-430
Power Factor	0.8
Voltage Regulation	%Within + 0.5
Excitation	Brushless, Rotating Exciter (with A.V.R.)
Insulation	Class F

ENGINE

Make & Model	Isuzu B-4BG1
Type	Inlined, Direct Injected
Output Rating	1500rpm 46.5 PS 34.2 KW
No. of Cylinders-Bore X Stroke	4-105 x 125mm
Piston Displacement	4.329L
Fuel	Diesel
Fuel Consumption	6.3 L/H
Lube Oil Sump Cap	14L
Coolant Capacity	25L
Battery Capacity	65D31RX2 V-Ah
Fuel Tank Capacity	100L

UNIT

Dimensions (L/W/H)	2000x880x1250mm
Dry Weight	1180kg

SOUND LEVEL

7m/dB (A) 1500rpm	(min-1)	64
-------------------	---------	----

GENERAL

The DCA series generators are complete, stand alone generating sets. All models consist of an alternator which is directly coupled to a diesel engine. The alternator and engine are set on a common skid base. Special Vibration isolators are used to minimize vibrations during operation. The generator and electrical components are fully enclosed in a solid steel, weatherproof canopy. Noise suppression is achieved by using highly effective sound insulation materials.

50HZ/60HZ OPERATION

The DCA series can be operated at either 50Hz or 60Hz by simply adjusting the engine speed using the throttle control knob on the control panel.

AUTO FUEL AIR EXTRACTOR

Air trapped in the fuel system can be troublesome. However, with the DCA series, fuel air extraction is Automatically performed by simply operating the starter switch, without the need for tools or devices. There is no soiling of the machines interior or the operators hands and the outflow of fuel to the machines exterior is prevented. The machine will start after the engine is turned over a few times.

EXTREMELY QUIET OPERATION

In urban areas and at the worksite, there is an ever increasing demand for reduced noise. The DCA series generators are extremely quiet when operating at full load.

CLEAN ENGINES

The engines used in these generators meet all Californian Atmospheric Pollution standards, which is one of the worlds most stringent antipollution standards. This is achieved by using a PCV purge control valve system. Therefore, these engines do not discharge blow-by gas to the outside, which keeps the interior of the machine cleaner and the exhaust emissions are minimized