



# REDSTAR™

Passionate about Value

PH 1800 REDSTAR

[www.redstarequipment.com.au](http://www.redstarequipment.com.au)

## Prime Mobile Generator 1100

1000 (kVA) 50HZ 1500RPM



### SPECIFICATIONS

#### ALTERNATOR

Frequency	50 (Hz)
Output Rating	Prime 1000 (kVA) Standby 1100 (kVA)
No. of Phases	Three Phase, 4 - Wire
Rated Voltage (V)	190/240
Power Factor	0.8
Excitation	Brushless, Rotating Exciter (With A.V.R)
Insulation	Class F

#### DIESEL ENGINE

Make & Model	Mitsubishi S12H-PTA
Type	V12 Direct Injected, Turbo Charged, After Cooled
Rated Output	890/1500 kW/imn <sup>-1</sup>
No. of Cylinders	12
Bores x Strokes	150 x 175mm
Displacement	37.11L
Fuel	Diesel Fuel
Fuel Tank Capacity	800 L
Fuel Consumption	154 L/h
Lube Oil Sump Cap	200L
Coolant Capacity	244L
Battery Capacity	190 H52x4 V-Ah

#### UNIT

Length/width/height	6000 x 2350x 2950
Dry Weight (kg)	14500

#### SOUND LEVEL

7m @ 1500rpm	72dB
--------------	------

#### GENERAL

The DCA series generators are complete, stand alone generating sets. All models consist of an alternator which is directly coupled to a diesel engine. The alternator and engine are set on a common skid base. Special Vibration isolators are used to minimize vibrations during operation. The generator and electrical components are fully enclosed in a solid steel, weatherproof canopy. Noise suppression is achieved by using highly effective sound insulation materials.

#### 50HZ/60HZ OPERATION

The DCA series can be operated at either 50Hz or 60Hz by simply adjusting the engine speed using the throttle control knob on the control panel.

#### AUTO FUEL AIR EXTRACTOR

Air trapped in the fuel system can be troublesome. However, with the DCA series, fuel air extraction is Automatically performed by simply operating the starter switch, without the need for tools or devices. There is no soiling of the machines interior or the operators hands and the outflow of fuel to the machines exterior is prevented. The machine will start after the engine is turned over a few times.

#### EXTREMELY QUIET OPERATION

In urban areas and at the worksite, there is an ever increasing demand for reduced noise. The DCA series generators are extremely quiet when operating at full load.

#### CLEAN ENGINES

The engines used in these generators meet all Californian Atmospheric Pollution standards, which is one of the worlds most stringent antipollution standards. This is achieved by using a PCV purge control valve system. Therefore, these engines do not discharge blow-by gas to the outside, which keeps the interior of the machine cleaner and the exhaust emissions are minimized