

**STANDBY POWER GENERATOR BAIFA BF-C412**



**SPECIFICATIONS**

**Alternator**

Frequency	50Hz
Output Standby/Continuous	412/375KVA
Rotating Speed	1500RMP
Number of Phase:	3
Connecting Type:	3 Phase and 4 Wires, "Y" type connecting
Number of Bearing:	1
Power Factor:	0.8
Protection Grade:	IP23
Altitude:	≤1000m
Exciter Type:	Brushless, self-exciting
Insulation Class, Temperature Rise:	H/H
Telephone Influence Factor (TIF):	< 50
THF:	< 2%
Voltage Regulation, Steady State:	±1%
Alternator Capacity:	400KVA
Alternator Efficiencies:	93%
Air Cooling Flow:	0.8m <sup>3</sup> /s

**Engine**

Manufacturer / Model:	CCEC Cummins NTAA855-G7, 4-cycle
Air Intake System:	Turbo, Air/Air cooling
Fuel System:	PT type fuel pump, EFC
Cylinder Arrangement:	6 in line
Displacement:	14L
Bore and Stroke:	140*152 ( mm )
Compression Ratio:	14.0:1
Rated RPM:	1500rpm
Max. Standby Power at Rated RPM:	377KW/513HP
Governor Type:	Electronic

**Unit**

Dimensions (L/W/H mm)	3020 (mm) *1440 (mm) *2200 (mm)
Dry Weight	4000kg

**General Features:**

Engine (CCEC Cummins NTAA855-G7 )

Radiator 50°C max, fans are driven by belt, with safety guard

24V charge alternator

Alternator: single bearing alternator IP23, insulation class H/H

Absorber

Dry type air filter, double fuel filter, oil filter, coolant filter

Main line circuit breaker

Standard control panel – Remote start.

Two 12V batteries, rack and cable

Ripple flex exhaust pipe, exhaust siphon, flange, muffler